

SILICABLE® RW

EN 50382-2 3600V FF 150 °C

Sheathed cable

HIGH TEMPERATURE POWERCABLES
EN 50382-2

- 1 • Flexible red copper core - class 5 - EN 60228.
- 2 • Separating tape (optional).
- 3 • Silicone rubber with high mechanical properties - type EI 111 as per EN 50382-1.
- 4 • Silicone rubber with high mechanical properties - type EM 107 as per EN 50382-1.

Characteristics

Thermal

Continuous operating temperature:
-40 °C at +150 °C.

Electrical

Operating voltage: 3.6 / 6 kV.
Test voltage: 11 kV A.C.

Mechanical

Cut-through resistance: ★★★★★
Resistance to alternate bending: ★★★★★☆
Resistance to abrasion: ★★★★★☆
Minimum static internal bending radius
(EN 50355): 5xD.

Chemical

Acid and base resistance: ★★★★★☆
Mineral oil resistance: ★★★★★☆

Fire-smoke

Halogen-free (EN 60754-1).
Low toxicity (EN 60754-2).
Low smoke (EN 61034-2).
Flame retardant (EN 60332-1-2, EN 60332-3-24).

Standards and approvals

- EN 60228, EN 50382-1, EN 50382-2.
- EN 60754-1, EN 60754-2.
- EN 60332-1-2, EN 60332-3-24, EN 61034-2.

Marking

OMERIN 369- EN 50382-2 3600V 1x < cross-section > FF 150 °C - batch number - week/year

Item code	Nominal cross-section (mm²)	Nominal stranding	Nominal insulation thickness (mm)	Nominal sheath thickness (mm)	Cable outer diameter (mm)		Maximum linear resistance at 20 °C (Ω/km)	Approx. linear weight (kg/km)
					Mini	Maxi		
A0828007	2.5	50 x 0.25	2.6	1.4	9.9	11.6	7.98	120
A0828008	4	56 x 0.30	2.6	1.4	10.4	12.2	4.95	140
A0823009	6	84 x 0.30	2.6	1.4	10.9	12.8	3.30	170
A0823010	10	80 x 0.40	2.6	1.4	11.8	13.8	1.91	220
A0823011	16	126 x 0.40	2.6	1.4	12.8	15.0	1.21	300
A0823012	25	196 x 0.40	2.9	1.4	14.7	17.2	0.78	420
A0823013	35	276 x 0.40	2.9	1.4	15.9	18.6	0.554	520
A0823014	50	396 x 0.40	2.9	1.5	17.5	20.5	0.386	690
A0823015	70	360 x 0.50	2.9	1.5	19.2	22.4	0.272	910
A0823016	95	485 x 0.50	2.9	1.6	20.8	24.3	0.206	1170
A0823017	120	608 x 0.50	2.9	1.6	22.4	26.2	0.161	1420
A0823018	150	756 x 0.50	2.9	1.7	24.1	28.2	0.129	1740
A0823019	185	944 x 0.50	3.2	1.8	26.4	30.9	0.106	2130
A0823020	240	1221 x 0.50	3.4	1.9	29.4	34.4	0.0801	2710
A0823021	300	1525 x 0.50	3.4	1.9	31.7	37.1	0.0641	3310
A0823022	400	2037 x 0.50	3.4	2.0	35.0	40.9	0.0486	4300

For this product, please contact :

OMERIN division principale

Zone Industrielle - F 63600 Ambert
Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10
omerin@omerin.com

OMERIN division silisol

BP 87 - ZI du Devev - F 42000 Saint-Etienne
Tel. +33 (0)4 77 81 36 00 - Fax +33 (0)4 77 81 37 00
silisol@omerin.com

www.omerin.com

omerin
LES CABLES DE L'EXTREME

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force.
For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.
© Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.