


ENERSYL® RH POWER

Multicore power cables



- 1 • Stranded bare copper core, class 2 as per IEC 60228.
- 2 • Optional separating tape.
- 3 • Insulation: PVC, type PVC/A as per IEC 60502-1 + optional filler(s).
- 4 • (optional) electrical screen: aluminium/PET tape + continuity wire (EG) / tin-plated copper braid (BE) / bare copper braid (BR).
- 5 • (optional) Internal sheath: Hydrocarbon resistant PVC, type ST1 as per IEC 60502-1.
- 6 • (optional) Bedding: waxed crepe paper.
- 7 • (optional) Armour: double steel tape (FA) / galvanized steel braid (BG).
- 8 • Outer sheath: Hydrocarbon resistant PVC, type ST1 as per IEC 60502-1.

Reference

- (example) ENERSYL® RH EG FA POWER 2x4 mm²
RH: Hydrocarbon resistant
EG, BE, BR: type of electrical screen
FA, BG: type of armour
POWER: power cable
2: number of conductors
X, G: type of assembly: without (X)
or with (G) an earth wire
4 mm²: cross-section in mm²

Approvals - standards

- IEC 60228 / IEC 60502-1.
• IEC 60332-1.
- Inspired by standard NF M 87-202 for oil industry.

Markings

- OMERIN – ENERSYL < RH xx xx POWER >
< cross-section > – 600/1000V – < batch > – < year >

Standard products

- Sheath: grey.
- Colour identification of conductors:
< up to 5 conductors: as per HD 308 S2.
> more than 5 conductors: black numbered.

Technical characteristics

Thermal

- Continuous operating temperature: -30 °C to +80 °C.

Electrical

- Rated voltage: 600/1000 V.
- Test voltage: 3500 V.

Fire

- Flame retardant – cable alone:
IEC 60332-1-2 / NF EN 60332-1-2 / NF C 32-070 test C2.

Resistance of outer sheath to chemical attacks as per OMERIN test report NT140404-01:

- Good resistance to acid.
- Good resistance to base.
- Excellent resistance to aliphatic hydrocarbons as per NF M 87-202.
- Excellent resistance to mineral oil in IRM 902.
- Resistance to water: type AD7 as per IEC 60529 without immersion of ends.

Options

- FLEX: flexible tin-plated copper core, class 5 as per IEC 60228.
- Other colours: contact us.

For this product, please contact:

OMERIN division principale

Zone Industrielle - F 63600 Ambert
Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10
omerin@omerin.com

OMERIN division silisol

BP 87 - ZI du Devevy - F 42000 Saint-Étienne
Tel. +33 (0)4 77 81 36 00 - Fax +33 (0)4 77 81 37 00
silisol@omerin.com

omerin
LES CABLES DE L'EXTREME

www.omerin.com

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.
® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.

NON-SHIELDED CABLES							ARMoured CABLES			
Nominal cross-section (mm ²)	Nominal stranding	Nominal thickness of insulation (mm)	Nominal diameter of conductors (mm)	Nominal thickness of the sheath (mm)	Nominal outside diameter* (mm)	Approximate linear weight (kg/km)	Nominal thickness of the sheath (mm)	Nominal outside diameter* (mm)	Approximate linear weight (kg/km)	Max. linear resistance at 20 °C (Ω/km)
2 x 1.5	7 / 0.52	0.8	3.1	1.8	10.3	121	1.8	14.7	292	12.1
3 x 1.5	7 / 0.52	0.8	3.1	1.8	10.8	147	1.8	15.2	325	12.1
4 x 1.5	7 / 0.52	0.8	3.1	1.8	11.6	175	1.8	16.1	369	12.1
5 x 1.5	7 / 0.52	0.8	3.1	1.8	12.5	204	1.8	17.0	411	12.1
7 x 1.5	7 / 0.52	0.8	3.1	1.8	13.4	255	1.8	17.9	475	12.1
12 x 1.5	7 / 0.52	0.8	3.1	1.8	17.1	398	1.8	21.6	673	12.1
19 x 1.5	7 / 0.52	0.8	3.1	1.8	19.7	572	1.8	24.2	885	12.1
24 x 1.5	7 / 0.52	0.8	3.1	1.8	22.8	707	1.8	27.5	1079	12.1
27 x 1.5	7 / 0.52	0.8	3.1	1.8	23.3	776	1.8	28.0	1154	12.1
37 x 1.5	7 / 0.52	0.8	3.1	1.8	25.9	1014	1.9	30.8	1446	12.1
2 x 2.5	7 / 0.67	0.8	3.6	1.8	11.3	151	1.8	15.8	341	7.41
3 x 2.5	7 / 0.67	0.8	3.6	1.8	11.9	189	1.8	16.4	386	7.41
4 x 2.5	7 / 0.67	0.8	3.6	1.8	12.8	229	1.8	17.3	441	7.41
5 x 2.5	7 / 0.67	0.8	3.6	1.8	13.8	271	1.8	18.3	497	7.41
7 x 2.5	7 / 0.67	0.8	3.6	1.8	14.9	345	1.8	19.4	587	7.41
12 x 2.5	7 / 0.67	0.8	3.6	1.8	19.2	547	1.8	23.7	852	7.41
19 x 2.5	7 / 0.67	0.8	3.6	1.8	22.2	800	1.8	26.7	1150	7.41
24 x 2.5	7 / 0.67	0.8	3.6	1.8	25.8	994	1.9	30.7	1425	7.41
27 x 2.5	7 / 0.67	0.8	3.6	1.8	26.3	1096	1.9	31.2	1535	7.41
37 x 2.5	7 / 0.67	0.8	3.6	1.8	29.4	1446	2.0	34.7	1965	7.41
2 x 4	7 / 0.85	1.0	4.7	1.8	13.5	211	1.8	18.0	432	4.61
3 x 4	7 / 0.85	1.0	4.7	1.8	14.3	269	1.8	18.8	502	4.61
4 x 4	7 / 0.85	1.0	4.7	1.8	15.6	336	1.8	20.0	583	4.61
5 x 4	7 / 0.85	1.0	4.7	1.8	16.9	400	1.8	21.4	671	4.61
7 x 4	7 / 0.85	1.0	4.7	1.8	18.3	517	1.8	22.8	809	4.61
12 x 4	7 / 0.85	1.0	4.7	1.8	23.8	827	1.8	28.3	1199	4.61
2 x 6	7 / 1.04	1.0	5.1	1.8	14.3	257	1.8	18.8	490	3.08
3 x 6	7 / 1.04	1.0	5.1	1.8	15.1	336	1.8	19.6	581	3.08
4 x 6	7 / 1.04	1.0	5.1	1.8	16.5	423	1.8	21.0	689	3.08
5 x 6	7 / 1.04	1.0	5.1	1.8	18.0	507	1.8	22.5	795	3.08
7 x 6	7 / 1.04	1.0	5.1	1.8	19.5	665	1.8	24.0	974	3.08
2 x 10	7 / 1.33	1.0	6.2	1.8	16.6	360	1.8	21.1	627	1.83
3 x 10	7 / 1.33	1.0	6.2	1.8	17.6	480	1.8	22.1	762	1.83
4 x 10	7 / 1.33	1.0	6.2	1.8	19.2	606	1.8	23.7	912	1.83
5 x 10	7 / 1.33	1.0	6.2	1.8	20.9	733	1.8	25.4	1064	1.83
2 x 16	7 / 1.68	1.0	7.3	1.8	18.8	494	1.8	23.3	793	1.15
3 x 16	7 / 1.68	1.0	7.3	1.8	20.0	673	1.8	24.5	990	1.15
4 x 16	7 / 1.68	1.0	7.3	1.8	21.9	859	1.8	26.4	1204	1.15
5 x 16	7 / 1.68	1.0	7.3	1.8	23.9	1046	1.8	28.4	1421	1.15
2 x 25	7 strands	1.2	8.7	1.8	21.6	696	1.8	26.1	1037	0.727
3 x 25	7 strands	1.2	8.7	1.8	23.0	966	1.8	27.5	1327	0.727
4 x 25	7 strands	1.2	8.7	1.8	25.3	1244	1.8	30.0	1653	0.727
5 x 25	7 strands	1.2	8.7	1.8	27.7	1523	1.9	32.6	1984	0.727
2 x 35	7 strands	1.2	9.5	1.8	23.2	894	1.8	27.9	1271	0.524
3 x 35	7 strands	1.2	9.5	1.8	24.7	1256	1.9	29.6	1670	0.524
4 x 35	7 strands	1.2	9.5	1.8	27.2	1627	1.9	32.1	2080	0.524
5 x 35	7 strands	1.2	9.5	1.9	30.1	2014	2.0	35.2	2526	0.524
2 x 50	19 strands	1.4	11.0	1.8	26.2	1186	1.9	31.1	1623	0.387
3 x 50	19 strands	1.4	11.0	1.8	28.0	1684	2.0	33.1	2163	0.387
4 x 50	19 strands	1.4	11.0	1.9	31.0	2205	2.1	36.3	2749	0.387
5 x 50	19 strands	1.4	11.0	2.0	34.3	2731	2.2	39.8	3347	0.387
2 x 70	19 strands	1.4	12.8	1.9	30.0	1590	2.0	35.1	2102	0.268
3 x 70	19 strands	1.4	12.8	1.9	32.0	2269	2.1	37.3	2831	0.268
4 x 70	19 strands	1.4	12.8	2.0	35.6	2977	2.2	41.1	3615	0.268
2 x 95	19 strands	1.6	14.8	2.0	34.2	2160	2.2	39.7	2775	0.193
3 x 95	19 strands	1.6	14.8	2.1	36.8	3119	2.3	42.3	3777	0.193

* The rated outer diameter of cables may vary by +/- 15% depending on the options selected (excluding FLEX option +/- 25%).